



EOBD 3000

Dimensiones Size	180x85x30 mm
Peso Weight	480 g
Normativas Approvals	CE (2004/108/EC) RoHS (2002/95/EC) ISO 15031-EOBD ISO 27145-WWH OBD Multiplexer function 2xHS CAN (ISO 11898-2) SW CAN (SAE J2411)
Protocolos Comunicación Communication Protocols	K/L (ISO 9141-2) VPW (J1850) PWM (J1850) RS485 (J1708) TTL (SPI, analog in, 5Volt out) Cable 1600mm, detachable with 16 pin Hd-sub
Conexión Vehículo Vehicle Connection	Connector ISO15031-3 (SAE J1962) with LED lamp (2 x CR1216 batteries)
Interfaz de Comunicación Communication Interface	USB Type B connector Bluetooth® range 30m Micro-SD Card Trigger Button Buzzer Multi-Colour indicator
Otros Others	
Alimentación Power Supply	Range: 6 - 36 V Max. 500 mA

EOBD 3000
Escaner Check CDP+ | Check CDP+ Scan Tool

Include
Includes

- Maletín Transporte | Carrying Case
- Dispositivo VCI | VCI Device
- DVD Software | Software DVD
- Dongle Licencia Check | Check License Dongle
- Conector 16 pin Luz LED | 16 pin Connector LED Light

OPCIONES | OPTIONS


Licencia 1 Año con Actualizaciones
1 Year User License with Updates



CARACTERÍSTICAS | FEATURES


Software Específico para ITV
PTI Specific Software Development

Maletín Transporte
Carrying Case



Conexión inalámbrica - Bluetooth
Wireless Connection - Bluetooth

Licencia 2 Años con Actualizaciones
2 Year User License with Updates



Conector con Luz LED
Connector With LED Light

Configuración Sistemas a Escanear
Systems to Scan Configuration



Integración Software VTEQ TestWin
VTEQ TestWin Software Integration



IMÁGENES | GALLERY

En Colaboración con:
In Collaboration with:



PANTALLAS | SCREENSHOTS

